

Specification Sheet for Denver™ Leathercloth

General Purpose UV Resistant Quality Fabric

Stock Code LCD

Width:	137 cm.
Thickness:	0.8 -1.0mm gauge
Roll Length:	30 metres (nominal).
Backing:	Double knit polyester/rayon for extra strength and flexibility.
UV Protection:	UV resistant quality fabric for general furniture, auto use.
Anti-Mildew:	Sanitized protection on backing to prevent mildew and bacterial growth.
Warranty	One year warranty against de-lamination/cracking.

Passed the Following Technical Specifications:

Test		Unit	Test Method	Min Spec.	Result Average
Actual Total Thickness		mm	Thickness gauge	0.85 ± 0.05	0.85
Total GSM		g/m ²	Weighting balance	550 ± 50	570
Tensile / Breaking Load	Long.	Kg	JIS K 6772	20.0	28
	Trans.	Kg	JIS K 6772	15.0	21
Elongation Break	Long.	%	JIS K 6772	40	92
	Trans.	%	JIS K 6772	150	200
Tearing Strength	Long.	Kg	JIS K 6772	3	4
	Trans.	Kg	JIS K 6772	2	3
Bonding Strength	Long.	Kg	JIS K 6772	1.5	2.3
	Trans.	Kg	JIS K 6772	1	1.4
UV Fade Resistance 63 ± 3c blue wool N ^o .6		Grey scale	AS 1411.11	Index 1 to 5	Grade 5

Notes: JIS: Japan Industrial Standard.
AS: Australian Standard.
Above test conducted on specimen obtained from actual production batch.