

Call Free 0508 222 999 (AKLD)





Specification Sheet for Surface Mount W/C Seatbelt Sign

Stock Code LPWCSB



FEATURES

- Two section bus sign indicator
- Fasten Seat Belt (FSB) and WC Occupied signs
- FSB sign 91/671/EEC compliance
- Any text or sign can be ordered
- Display area 2x (75 x 48) mm
- Illuminated by SMD LEDs

APPLICATIONS

• FSB and WC sign for vehicles (buses, trains, yachts)

Nominal Supply 24 VDC 12 VDC Voltage Supply Voltage 1832 VDC 916 VDC
Voltage Supply Voltage 1832 VDC 916 VDC
1 1 2 1 1 2 1 1 2 1 1 1 1 1 1 1 1 1 1 1
Range Supply Current100 mA max.190 mA max.
FSB Supply Current WC 80 mA max. 150 mA max.
Display Illumination FSB: White SMD LEDs, WC: Red SMD LEDs
Display Area 72 x 48 mm 2 sections.
Temperature Range -40 ∘C+80 ∘C
Relative Humidity 95 %
Dimensions 210 (L) x 87 (H) x 21.5 (D) mm
Weight 170 gr

Connection: 6.3 mm (male) standard automotive connectors according to DIN 46340 / 46343

Specifications are subject to change without notice

