

## Specification Sheet for Borflor Vinyl Flooring

**Suitable for industrial applications where a hard wearing non slip surface is required.**

### **Stock Code MGVF (excludes Woodgrain)**

<b>Material:</b>	PVC vinyl flooring with Quartz sand. Fabric backing. Abrasion resistant. 0.9mm wear layer. Chemical and slip resistant. Easy to clean.
<b>Width:</b>	200cm
<b>Roll:</b>	20 metres
<b>Warranty:</b>	8 years
<b><u>Typical Performance:</u></b>	
<b>Nominal Thickness:</b>	2mm
<b>Weight (floor covering only):</b>	2.8kg/m <sup>2</sup>
<b>Abrasion Resistance:</b>	0.9mm
<b>Smoke &amp; Fire Resistance/Toxicity:</b>	Meets GB8624-2012 and BS476 Class 3
<b>Elongation:</b>	>=50%
<b>Slip Resistance:</b>	Slip Resistance TRRL Pendulum European Standard EN13036 Dry 122 Wet 71 DIN51130 Slip Resistance Oil/Wet Ramp Test critical angle inclination 10.7degrees classification R10
<b>Hardness:</b>	Frontage >=78 Backing >=75
<b>Tearing Strength:</b>	>=45N/mm