

## Specification Sheet for 100% Polyester Transport Fabric

140 cm Wide

Stock Code SFTPB

<b>Composition:</b>	100% Polyester.
<b>Tensile Strength (BS2576: 1986):</b>	<b>Warp:</b> 881 N. <b>Weft:</b> 1760 N.
<b>Tear Strength (BS4303: 1968):</b>	<b>Warp:</b> 107 N. <b>Weft:</b> 87 N.
<b>Seam Slippage (BS3320: 1970):</b>	<b>Warp 18 kg:</b> 4 mm. <b>Warp 0.25 kg:</b> 3 mm. <b>Weft 18 kg:</b> 4 mm. <b>Weft 0.25 kg:</b> 3 mm.
<b>Colour Fastness to Rubbing (BS 1006: 1990 x 12):</b>	<b>Dry Rubbing:</b> Warp/Weft: 4-5. <b>Wet Rubbing:</b> Warp/Weft: 4-5.
<b>Colour Fastness to Light (BS 1006: 1978B01):</b>	5.
<b>Abrasion Resistance (BS5690: 1991):</b>	80,000 rubs.
<b>Weight:</b>	600 grams per square metre +/- 8%.
<b>Yarn Count/Denier:</b>	300D (G) 20/2 (P & F).
<b>Density W x W:</b>	19/1" x 47/1".
<b>Colours:</b>	Bojangles Lagoon Bojangles Midnight Bojangles Storm Bojangles Pacific Blue