

Specification Sheet for Boatmaster® Plain and Coated RECacril®

UV Resistant Acrylic Canvas

Stock Code CVAR and CVACR

Fabric:	100% Solution Dyed Acrylic		
Finish:	Fluorocarbon/Resin		
Mass:	Finished: Plain - 305gr/m ² Coated - 330gr/m ²	UNE 53352	
Width:	120cm, 150cm, 200cm		
Roll Length:	Plain 120cm wide 60m 200cm wide 40m Coated 150cm wide 60m		

Typical Performance:

Strength:

		Plain	Coated
Tear Strength UNE53326	+/- 10%	Warp 5kg (49N) Weft 3kg (29N)	Warp 5kg (49N) Weft 4kg (39N)
Tensile Strength UNO EN ISO 13934-1	+/- 5%	Warp 150kg/5cm (1471N) Weft 85kg/5cm (834N)	Warp 150kg/5cm (1471N) Weft 90kg/5cm (883N)

Oil repellency:	≥4	
Xenotest:	4 – 5	UNE EN ISO105B04
Bundesmann:	4 – 5	UNE EN29865
Colour Fastness:	7 - 8	UNE EN ISO105B02
Abrasion:	40,000 rubs	
Water Column:	Plain ≥350mm Coated ≥1000mm UNE EN ISO 20811	
Ultraviolet Protection Factor (UPF):	average of 80	
Limited Warranty:	8 years	