

## Specification Sheet for Awning & Shade RECacril® by S.A. Recasens

### UV Resistant Acrylic Canvas

### Stock Code CVAR and CVAS

|                     |  |           |
|---------------------|--|-----------|
| <b>Fabric:</b>      | 100% Solution Dyed Acrylic             |           |
| <b>Finish:</b>      | Fluorocarbon/Resin                     |           |
| <b>Mass:</b>        | Finished: Plain - 305gr/m <sup>2</sup> | UNE 53352 |
| <b>Width:</b>       | 120cm                                  |           |
| <b>Roll Length:</b> | Plain - 40m                            |           |

### Typical Performance:

#### Strength:

|   |         | Plain  |
|---|---------|--|
| <b>Tear Strength</b><br>UNE53326              | +/- 10% | Warp 5kg (49N)<br>Weft 3kg (29N)               |
| <b>Tensile Strength</b><br>UNO EN ISO 13934-1 | +/- 5%  | Warp 150kg/5cm (1471N)<br>Weft 85kg/5cm (834N) |

|   |  |                  |
|---|--|------------------|
| <b>Oil repellency:</b>                      | ≥4   |                  |
| <b>Xenotest:</b>                            | 4 – 5  | UNE EN ISO105B04 |
| <b>Bundesmann:</b>                          | 4 – 5  | UNE EN29865      |
| <b>Colour Fastness:</b>                     | 7 - 8  | UNE EN ISO105B02 |
| <b>Abrasion:</b>                            | 40,000 rubs                                  |                  |
| <b>Water Column:</b>                        | Plain ≥350mm Coated ≥1000mm UNE EN ISO 20811 |                  |
| <b>Ultraviolet Protection Factor (UPF):</b> | average of 80                                |                  |
| <b>Limited Warranty:</b>                    | 10 years                                     |                  |