

## Specification Sheet for Denver GT 4 Way Stretch Vinyl

### Stock Code LCD4BK

<b>Face Fabric:</b>	PVC
<b>Width:</b>	137 cm.
<b>Weight:</b>	608gsm.
<b>Thickness:</b>	1.15+-0.05mm
<b>Chemical resistance:</b>	Chlorine grey scale 5
<b>Abrasion resistance:</b>	Martindale Abrasion Resistance Class 5 commercial heavy duty AS2687: 50,000 cycles
<b>UV resistance:</b>	Grade 4+ -- ISO 4892-3:2006
<b>Cold crack:</b>	-30°C
<b>Anti-Microbial:</b>	Grade 3-4 -- ASTM G21-15
<b>Tensile Strength:</b>	Warp > 283.80 (N/30mm) Weft > 149.20 (N/30mm) -- GB/T8948-2008
<b>Breaking Elongation:</b>	Warp > 94 (%) & Weft > 300.60 (%) -- GB/T8948-2008
<b>Tear Strength:</b>	20.44 (N) & Weft > 15.84 (N) -- GB/T8948-2008
<b>Adhesion:</b>	Warp > 28.07 (N/30mm) Weft > 14.90 (N/30mm) -- GB/T8948-2008
<b>Cleaning instructions:</b>	Recommend regular cleaning with chemically neutral soap and warm water, and wipe or rinse clean. Cleaning products containing acetone must be avoided.