

www.retwine.co.nz

## **Specification Sheet for Bradmill Outdoor Fabrics 10 373 200 XLP Superdux®**

## **General Purpose Polyester/Cotton Utility Canvas**

Stock Code CVBSD12

Finish: **XLP** Pigment coloured, waterproofed and rot proofed.

**Fibre Content:** 52% Polyester, 48% Cotton.

Weave: Plain

Mass: 420 g/m<sup>2</sup> (12.4 oz/yd<sup>2</sup>) Nominal Loomstate:

 $510 \text{ g/m}^2 (15.0 \text{ oz/yd}^2)$ Proofed:

Width: 200 cm

**Roll Length:** 50 m

## Typical Performance:

Strength:

	Test Method	Warp	Weft
Breaking Force (N)	AS2001.2.3A	2500	1800
Tearing Force (N)	AS2001.2.10	110	70

Water Resistance: Hydrostatic pressure (kPA) (AS2001.2.17): 10+

Cone leakage (ml) (AS2001.2.18): 0

Shrinkage: Relaxation shrinkage (%): Warp: -3.0

Weft: -0.5

Relaxation shrinkage test results provide a good guide as to how the canvas will react to everyday use and are useful in determining the best way to cut and style products.

**Colour Fastness:** Light fastness (AS2001.4.21): 6-7

> Rub fastness (AS2001.4.3): Dry 3-4

Wet 4

Total Colour Difference (compared to nominated standard): CMC 2:1 DE <1.0

