REID & TWINAME MPORTERS & DISTRIBUTORS Leaders in Motor Body Hardware, Automotive, Marine & Outdoor Textiles Call Free 0508 222 999 (AKLD) 0508 333 111 (CHCH) www.retwine.co.nz

Heng's 14 x 14 Vents

Ideal for motorhomes and vans.

- » Easy to operate crank handle.
- » Wire gauze screen.
- » Weather strip seal.

Plastic/Smoke Top Deep Garnish Vent

- » Cut Out Size: 359mm x 359mm.
- » Deep Garnish Roof thickness
 60 100mm.
- » Plastic frame.
- » Smoke top.

VTE14PSA2

Powder Coated Metal Vent/Deep Garnish

- » Cut Out Size: 354mm x 354mm.
- » Deep Garnish Roof thickness 60 -100mm.
- » Powder coated metal frame.
- » Smoke top.

VTE14JMSA2

Heng's 14 x 14 Vent PCM/White Dome

- » Cut Out Size: 354mm x 354mm.
- » Standard Garnish Roof thickness
 20 65mm.
- » Powder coated metal frame.
- » White dome top.

VTE14JW



Proudly New Zealand owned since 1923

Mobile Home Door Locks

- » Southco R3 push to close lock. Separate dead bolt, lockable from the inside. Very secure. Max working load 560N.
- » Recessed Exterior Handle. Die Cast, Zinc Alloy with a Powder Coat Finish. Lockable deadbolt from the inside as well as the outside.
- Width = 94mm. Height = 114mm. Suitable for door thickness's between 32 and 38mm. Cut out 68mmW x 92mmH, 32mm back from door edge.

LK60250 | LK60250BLK



Paddle Handle Slam Lock Stainless Steel

- » Stainless steel pan and handle. Zinc plated locking mechanism. Single point locking.
- » Overall size 140mm x 108mm. Depth 40mm. Cut out 112mm x 85mm. Tongue length 28mm. FS880 key number.
- » Rubber seal.

LKV388



Don't forget to follow us on facebook! Find us on F Reid & Twiname

Auckland: 7 Arthur Brown Place, Mt Wellington 1060 • PO Box 11 2230, Penrose, Auckland 1642 Christchurch: 15 Watts Road, Sockburn 8042 • PO Box 11 132, Sockburn, Christchurch 8443

Moulded Grab Rails

Moulded in expanded polyurethane foam with granular finish over spring steel core.

- » Overall length 300mm. Width 102mm. Height 75mm. Hole centres 165mm and 213mm. Thickness 25mm.
- » Load rating 377kg before distortion with horizontal fixing. Vertical fixing 363kg before distortion.
 Recommended safe working load of 250kg.

HNGR1225 | HNGR1225Y



- » Overall length 475mm. Width 90mm. Height 75mm. Hole centres 327mm and 375mm. Thickness 33mm.
- » Load rating 353kg before distortion with horizontal fixing. Vertical fixing 352kg before distortion. Recommended safe working load of 250kg.

HNGR901226



Grab Handle Die Cast

- » Chrome plated die cast Grab Handle 150mm overall.
- » Hole centres 130mm. Base width 30mm. Height 35mm.

HNGR1197



Polypropylene Pull Handle

- » Black polypropylene handle.
- » Concealed fixing with snap closed covers. Textured finish.
- » Overall length 170mm. Width 28mm Height 40mm. Fixing centres 137mm.

HNPPH



redflag

Hydraulic Oil Tank 125L

- » Polished alloy with single heavy straddle bracket/ 2 straps.
- » Both tank top and remote filter fittings 2" BSPT fittings chassis facing.
- » 340mm width x 754mm deep x 751mm high.
- » Includes mounting bracket, tank top filter will be extra.
- » Comes complete with Filler Breather.
- » Oil level indicator with thermometer can be mounted on the left or right side of tank.

HTAS125



Tank Top Return Filter OMT 17 Series



redflag

Tool Box Stainless Steel

- » 600L x 400H x 500D.
- » Quality 304 stainless steel truck tool box.
- » 2B matt finish on body and polished door.
- » Quality locking drop-t handle with dust cover.

REID&

- » Box has dust and weather seal fitted.
- » Covered lanyard included.
- » Spare parts available.

TBSS600



Call Free 0508 222 999 (AKLD) 0508 333 111 (CHCH)

WINAM