



Industrial
& Transport
Engineering
Supplies



A DIVISION OF

Call Free 0508 222 999 (AKLD) 0508 333 111 (CHCH)
www.retwine.co.nz

August 2021

Proudly New Zealand owned since 1923



Seat Belt Kit

- » Emergency locking retractor seat belt for bus and coach passenger seat market. Seat belt complies with AS/NZS2596.
- » Fits Vogel manufactured seats. Comes with a belt, mounting housing, guide for top of seat, has a stem 135mm included. Works for both left and right seat types. 0-0 deg working angle, this can be used in different seating situations not just Vogel seats.

STSBKC8766

Indytrilås
When access counts



Compression Latch

- » Sealed Flush Mounted.
- » Latch is sealed against water and dust IP65 protection.
- » Adjustable grip range 11 - 28mm. Suitable for panel/door thickness up to 7mm.
- » Face size 113mm x 58mm at the top and tapers down to 49.5mm at the bottom.
- » Cut out size is 90mm x 35mm.
- » Housing made from Glass reinforced polyamide (PA6).

ON SPECIAL THIS MONTH
1 at \$19.95 per unit
10 at \$18.95 per unit
25+ at \$17.95 per unit

LKCLIBK



Widney



Electric Bus Blind

- » 24v Electric Blind.
- » 1500mm fabric wide, 1000mm drop
- » Top 800mm section mesh, bottom 200mm solid black PVC.
- » Motor and blind setting instructions available on the website as a download.

BLWE1500



D Shape EPDM Sponge Seal



- » EPDM sponge seal extrusion with acrylic tape applied.
- » 17.5mm wide x 17.5mm high.
- » D Shaped seal has 2 legs for double protection sealing against panels, ideal for weather sealing doors.
- » Working temperature -40 to +110 deg celcius.
- » Sold by the 33m roll or in 5m increments.

RBSA50362



Auckland: 7 Arthur Brown Place, Mt Wellington 1060 • PO Box 11 2230, Penrose, Auckland 1642
Christchurch: 15 Watts Road, Sockburn 8042 • PO Box 11 132, Sockburn, Christchurch 8443

Rocker Action Pump Black

- » Self priming. Mounting hole 51mm. Length below Mounting Surface 120mm. Height from Mounting Surface 140mm.

PUPWS63



Double Action Pump

- » Self priming. Mounting Hole: 33 mm. Length Below Mounting Surface: 220 mm. Height From Mounting Surface: 115 mm.

PUPWS67



Supersub 88 Submersible 12v

- » 12 volt, 2.6 Ampt (Int). The Submersible pump with the bigger performance motor giving a greater water pressure. Just place the Supersub 88 pump inside the water tank. It is completely water sealed and, being totally submerged, there are no priming problems.
- » The Whale Supersub 88 works quietly and efficiently from a 12 volt DC Supply. Suitable for use with water heaters and for a shower.

PUGP8815



Superline 99 12v DC 3Amp

- » A compact highly efficient centrifugal pump with a performance capability that belies its size. Fits inline into existing hand or foot operated systems, and light enough to be suspended in the pipe work. When fitted below level of water tank it can be primed by gravity, eliminating the need for a manual priming pump. Unit is completely sealed to avoid damage from damp atmosphere or casual water.

PUGP9955



redflag™

Hydraulic Tank Polished Alloy 180L

- » Polished alloy hydraulic oil tank with heavy straddle brackets. Both tank top and remote filter fittings 1¼" BSPT fittings chassis facing. 775mm width x 550mm diameter. Note: HTFB - Filler Breather is needed with this tank.

- » Baffle titled

HTA180



GRAMMER

Maximo M MSG85/721 Mechanical Suspension Seat – Vinyl

- » Suitable for Forklifts, Construction machinery and Tractors. Mechanical suspension 80mm suspension stroke, manual weight adjustment, with seat belt and limit switch, mechanical lumbar support, adjustable back rest, seat cushion width 480mm. GRAMMER part number 1012109.

STGMAXMV



Call Free

0508 222 999 (AKLD) **0508 333 111** (CHCH)

REID & TWINAME
IMPORTERS & DISTRIBUTORS

*Specials are until 31st August 2021 and whilst stocks last. Prices are Trade and ex warehouses and are exclusive of GST.

www.retwine.co.nz