



Call Free **0508 222 999** (AKLD) **0508 333 111** (CHCH) **www.retwine.co.nz** 

May 2024

**Proudly New Zealand owned since 1924** 


# (APV-S) SAFETY PRODUCTS

### Seat Belt Kit

- » 0/0 degree retractable kit
- » Includes 135mm stem
- » Fits situations where the below example of retractor is mounted
- » After market for Vogel seats, Brusa Seats and many
- » Universal left and right

#### STSBKC8766





### Blinds

- » Left or right pull cord release
- » 1080 wide with 700mm drop

#### BLRSC1080L/R



# Lashing Ring

- » Dimensions 102mm x 95mm
- » Hole Size 74mm x 79mm
- » Recess 25mm
- » Anti rattle spring





### Antiluce Fastener

- » 304 grade Stainless Steel Antiluce Fastener
- » 12mm x 25mm thread
- » 6mm between toggle and mounting surface
- » Please NOTE these do not come with M12 nut

#### FTANTI3263SS



# Spring Bolt

- » 304 stainless steel.
- » Height 26mm. Bolt length 141mm.
- » Bolt diameter 10mm. Bolt travel 34mm,
- » Base width 40mm. Base length 72mm



**CT839SS** 







### Maximo SE MSG95G/721 12V Tractor Seat

- » Air suspended comfort seat with mechanical lumbar support
- » Suspension travel 100mm
- » Manual weight adjustment (50kg 130kg)
- » Air supported combined stepless height adjustment 80mm
- » Wide seat cushion (480mm)
- » Height and angle adjustable armrests (65mm x 270mm)
- » Fore/aft isolator
- » Adjustable backrest angle
- » Does not include the headrest and headrest is not stocked in NZ

### **STGMAXSE**





### Tool Box Powder Coated

Quality black powder coated 1.5mm mild steel truck or ute toolbox. Two robust stylish drop tee locks with dust cover for the key lock fitted to bevel edged door.

- » 1000L x 500H x 500D
- » Box weight 33kgs

#### **TBPC1000**



# Tool Box Angle Brackets

- » Black powder coated 75mm x 4mm C section, 500mm x 500mm cross braced.
- » Sold as a pair


#### **TBBKT**

**WNRFDS** 



# Replacement Door Seal

» Sold in 5m increments or 50m rolls.



WNRFDS

Call Free **0508 222 999** (AKLD) **0508 333 111** (CHCH)

